

SPAN

# SPAN Panel™

The smarter electrical panel

Monitor & control  
every circuit

Unprecedented home  
energy insights

Fully customizable backup  
when paired with storage



---

## Electrical

- Revenue accurate energy monitoring
- 100 - 200A main breaker
- 225A bussing

## Installation

- Indoor and outdoor rated
- Surface or semi-flush mounted
- Compatible with standard 1" breakers

## Connectivity

- Ethernet, WiFi, Cellular
- Free over-the-air updates

---

## Intuitive control

SPAN goes beyond monitoring with the SPAN Home App for real-time control and energy insights to bring your home's energy to life.

Combined with battery storage, SPAN gives homeowners the power to choose and change backup priorities whenever they want.

SPAN

## SPAN Panel dimensions



## Performance Specifications

AC Voltage (Nominal)	120/240V
Grid Connection	Split Phase
Grid Frequency	60 Hz
Disconnect Current	200 A
Busbar Rating	225 A
Sub-feed Lug Rating	200 A max
Max Input Short Circuit Current	22 kA <sup>1</sup>
Main Overcurrent Protection Device	100-200 A Breaker <sup>2</sup>
Controllable Circuits	32 (90 A max per breaker) <sup>3</sup>
Overvoltage Category	Category IV
AC Metering	ANSI revenue accurate (+/- 0.5%)
Primary Connectivity	Ethernet, WiFi (2.5, 5 GHz)
Secondary Connectivity	Cellular (4G/LTE, 3G)
User Interface	SPAN Home App (iOS, Android)
Limited Warranty	10 years

<sup>1</sup>22 kA RMS symmetrical with main breaker installed, otherwise 10 kA.

<sup>2</sup>Service Entrance Rated when main breaker installed.

<sup>3</sup>Compatible with tandem/quad style breakers at all positions.  
Monitoring and control is combined when used.

## Additional Features

- Compatible with SPAN Drive Lvl. 2 EVSE
- Customizable whole-home battery backup
- Backup time remaining estimates
- Real-time load control
- Energy monitoring & insights
- Load management for upgrade avoidance

## Become an Authorized Installer

SPAN is designed to completely replace the traditional electrical panel for new build or retrofit. The SPAN Installer App allows for simple installation and same-day commissioning, all in one place.

Learn more: [techportal.span.io](https://techportal.span.io)



## Environmental Specifications

Operating Temperature	-22 to 122°F (-30 to 50°C) <sup>4</sup>
Operating Humidity (RH)	Up to 100% condensing
Maximum Elevation	3000 m (9842 ft) <sup>4</sup>
Environment	Indoor and Outdoor rated
Enclosure Type	NEMA 3R

<sup>4</sup>Panels installed above 2000 m must be installed in ambient temperatures less than 104°F (40°C).

## Mechanical Specifications

Enclosure Dimensions	39.3 x 14.3 x 6.0 in (998 x 362 x 153 mm)
Flush Trim Kit Dimensions	44.2 x 15.9 in (1123 x 405 mm)
Mounting Options	Wall mounted, semi-flush or surface
Weight	75 lbs (34 kg)

## Compliance Information

Certifications	UL 67, UL 916, UL 869A
Emissions	FCC Part 15 Class B
Other	NEC compliant Energy Management System (EMS)